




H2K

INTERNATIONAL

**300x
300mm**

300 x 300 mm



WHITE



IVORY




GREY



BLUE



PINK



P.GREEN



COPER CLOUDY



RED BROWN



MAGENTA



B.GREEN



AL.BLUE



BLACK



AS.WHITE




AS.IVORY




AS.GREY



AS.BLUE



AS.PINK



AS.P.GREEN



Special Anti Skid Series...



AS.RED BROWN



AS.MAGENTA



AS.B.GREEN



AS.AL.BLUE



AS.BLACK

300 x 300 mm




6001



6002



6003



6004



6005




6006



6025



6026



6027



6028



6029

AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

03

300 x 300 mm



6102



6103




6104



6105



6106



6151



6152



6153



6155



300 x 300 mm



6125



6126



6128




6175




6176

300 x 300 mm




6202



6204




6205




6206

Special Swastik
Series...



6228



6229



300 x 300 mm



6252



6253



6254



6256

Special Docomo
Series...



6276



6278


300 x 300 mm



6302



6303



6304



6305



6306


Special Zeta
Series...




6325



6326



6327



6328



AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

08

300 x 300 mm



7001



7002



7003



7004



7005



7006



7007



7008



7009



7010



7011



7012

AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

11

300 x 300 mm



7013



7014



7015



7016



7017



7018



7019



7020



7021



7022



7023



7024

AN ISO 9001 : 2008 CERTIFIED COMPANY


Live a Natural Life

12

300 x 300 mm



7025



7026




7027



7028



7029



7030



7031



7032



7033



7034



7035



7036



AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

13

300 x 300 mm



7201



7202



7203



7204



7205



7206



7207



7208



7209



7210



7211



7212

AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

15

300 x 300 mm



7213



7214



7215



7216



7217



7218



7219



7220



7221



7222



7223



7224

AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

16

300 x 300 mm



7225



7226



7227




7228



7229



7230



7231



7232



7233



7234



7235



7236

AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

17



300 x 300 mm



7401



7402



7403



7404



7405



7406



7407



7408



7409



7410



7411



7412

AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

19

300 x 300 mm



7413



7414



7415



7416



7417



7418



7419




7420




7421



7422



7423



7424

AN ISO 9001 : 2008 CERTIFIED COMPANY

Live a Natural Life

20

300 x 300 mm



7601



7602



7603



7604



7605



7606



7607



7608



7609



7610



7611



7612

300 x 300 mm



7613



7614



7615



7616



7617



7618



7619




7620



7621



7622



7623



7624

300 x 300 mm



8001



8002



8003



8004



8005



8006



8007



8008



8009



8010



8011



8012

300 x 300 mm



TECHNICAL SPECIFICATION

Characteristics	Permissible Tolerance as per EN & IS norms	Typical Value of
Dimensional Tolerance	± 0.5% Max	±0.5% Max
Thickness Tolerance	a) Avg. of each tiles +0.6mm for >250 to 500m ² b) Avg. of each tiles +0.7mm for tile >500 to 1000cm ²	±0.5% Max
Straightness Tolerance Rectangularity Surface Flatness a) Center Curvature b) Edge Curvature c) Warpage Related to Diagonal Surface Quality	± 0.3% max ± 0.5% max ± 0.5% max ± 0.5% max ± 0.5% max min. 95% area should be free from visible defects	± 0.3% max ± 0.5% max ± 0.5% / -0.3% max ± 0.5% / -0.3% max ± 0.5% max min. 95% area should be free from visible defects
Water Absorption Modules of Rapture MOH's Scratch Hardness Crazing Resistance	± 10% Avg. 15N/mm ² Min. 3 1 Cycle of 1 hour at 5 bar steam pressure	>15% Avg. 20N/mm ² Min. 3 No crazing after 1 cycle of 1 hour at 5 bar steam pressure.
Water Absorption Modules of Rapture MOH's Scratch Hardness Crazing Resistance	±10% Avg. 15N/mm ² Min. 3 1 Cycle of 1 hour at 5 bar steam pressure.	>15% Avg. 20N/mm ² Min. 3 No crazing after 1 cycle of 1 hour at 5 bar steam pressure.
Chemical Resistance	Resistance to all acids & alkalies (Except Hydrofluoric acid & its compounds)	Resistance to all acids & alkalies (Except Hydrofluoric acid & its compounds)

PACKING DETAILS

Dimension	Thickness (mm)	Tiles Per Box Pcs.	Area Coverage Per Box (Sq.m.)
300 x 300mm	7.00 (Approx)	10	0.90 (Approx)

Notes : • Shade/size variation is inherent in ceramic tiles. In case of any complaint, it should be brought to our dealer's notice before laying the tiles.
• Colours shown are indicative only. Check actual tile for exact colour.